





Hints and features:

- The Sailun S696 is a truck tyre for trailer axles
- Its special rubber compound, wide tread and extra wide tyre shoulder enable slow and even wear and thus a long service life for the tyre
- Small sipes in the tread enable low heat generation and excellent grip in all weather conditions
- The circumferential zigzag-shaped grooves eject small stones and prevent the tyre from being damaged

REIFEN 445 / 65 R 22.5 20 PR, 169 K, TL, S696, M+S SAILUN (TR)

Product-No.: 11066410

## **Technical Information:**

Tyre size	445 / 65 R 22.5
TL/TT	TL
LI/SI	169 K
PR	20
Tread	S696
Manufacturer	Sailun
Specification	M+S
Recom. Rim	13.00
Permissible rim	14.00
Width [mm]	444
Outer diameter [mm]	1150
Payload in kg at kph (1)	5800 / 110
Inflation pressure [bar]	9,00
Weight [Kg]	95,01
Rolling resistance	С
Wet grip	В
Rolling Noise DB	72
Stud height [mm]	15,5
Zulassung	ECE 54, ECE 117
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.