





Hints and features:

- The Traxion 85 is a standard tractor tyre for mid-range tractors
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil
- Its flexible casing ensures a big contact area for good ground pressure distribution
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

REIFEN 340 / 85 R 38 133 A8 / 133 B, TL, TRAXION 85 (13.6R38), ECE106

Product-No.: 14826400

Technical Information:

Tyre size	340 / 85 R 38
TL / TT	TL
LI/SI	133 A8 / 133 B
Tread	TRAXION 85
Manufacturer	Vredestein
Recom. Rim	W12
Permissible rim	W11, DW12
Width [mm]	360
Outer diameter [mm]	1550
Static radius [mm]	730
Rolling circumference [mm]	4680
Payload in kg at kph (1)	2060 / 40
Payload in kg at kph (2)	2060 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	89,68
Tyre content 75% [litre]	170
Stud height [mm]	41,0
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.