





Hints and features:

- The Traxion 85 is a standard tractor tyre for mid-range tractors
- Its special tread pattern with curved lugs and rounded shoulders enables high traction while protecting the soil
- Its flexible casing ensures a big contact area for good ground pressure distribution
- Its special casing construction with increased volume allows for increased load capacity compared to the older generation standard tyres
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds or on slopes
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

REIFEN 480 / 80 R 42 156 A8 / 156 B, TL, TRAXION 85 (18.4R42), ECE106

Product-No.: 14826530

Technical Information:

Tyre size	480 / 80 R 42
TL/TT	TL
LI / SI	156 A8 / 156 B
Tread	TRAXION 85
Manufacturer	Vredestein
Recom. Rim	DW16L
Permissible rim	DD16L, W16L
Width [mm]	500
Outer diameter [mm]	1850
Static radius [mm]	855
Rolling circumference [mm]	5600
Payload in kg at kph (1)	4000 / 40
Payload in kg at kph (2)	4000 / 50
Inflation pressure [bar]	2,40
Weight [Kg]	177,7
Tyre content 75% [litre]	490
Stud height [mm]	49,0
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.