Bohnenkamp Moving Professionals



Hints and features:

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road

REIFEN 12.5 / 80 - 15.3 14 PR, 142 A8, TL, SG-316, AW ECE 106

Product-No.: 19111120

Technical Information:

Tyre size	12.5 / 80 - 15.3
TL / TT	TL
LI / SI	142 A8
PR	14
Tread	SG-316
Manufacturer	Deli
Recom. Rim	9.00
Width [mm]	310
Outer diameter [mm]	889
Static radius [mm]	384
Rolling circumference [mm]	2676
Payload in kg at kph (1)	2650 / 40
Inflation pressure [bar]	4,30
Weight [Kg]	24,96
Stud height [mm]	9,5
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.