



Hints and features:

- The Alliance Agro Industrial 580 CRC is an agro industrial / MPT tyre for telescopic, wheel and backhoe loaders
- The steel belted construction enables high load capacities and maximum stability in use
- The tread pattern with angled center lugs provides strong grip and ideal traction on soft and hard surfaces
- Thanks to the cut-resistant rubber compound, the tyre is extremely puncture and wear resistant and durable even in tough operating conditions
- Ideal for biogas plants

REIFEN 460 / 70 R 24

159 A8 / 159 B, TL, AGRO INDUSTRIAL 580
(17.5LR24), CUT RESISTANT, ECE106

Product-No.: 15285312

Technical Information:

Tyre size	460 / 70 R 24
TL / TT	TL
LI / SI	159 A8 / 159 B
Tread	Agro Industrial 580
Manufacturer	Alliance
Specification	C.R./Steel Belted
Recom. Rim	DW15L
Permissible rim	DW14L
Width [mm]	462
Outer diameter [mm]	1250
Static radius [mm]	567
Rolling circumference [mm]	3701
Payload in kg at kph (1)	4375 / 40
Payload in kg at kph (2)	4375 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	107,8
Stud height [mm]	39,5
Number of studs	17x2
Zulassung	ECE 106
Direction bound	Yes