

Mitas

REIFEN 460 / 65 R 22.5  
158 A8 / 168 A8, TL, AR-01

Product-No.: 10915500



Hints and features:

- The Mitas AR-01 is a radial implement tyre for towed agricultural trailers with speeds up to 80 km/h
- Due to the special block tread and the big contact area, the soil is optimally protected
- The strong casing ensures durability and a long service life

Technical Information:

Tyre size	460 / 65 R 22.5
TL / TT	TL
LI / SI	156 A8 / 168 A8
Tread	AR-01
Manufacturer	Mitas
Recom. Rim	14.00
Width [mm]	450
Outer diameter [mm]	1.170
Static radius [mm]	550
Rolling circumference [mm]	3456
Payload in kg at kph (1)	4000 / 40
Payload in kg at kph (2)	5600 / 40
Inflation pressure [bar]	5,00
Weight [Kg]	84,4
Stud height [mm]	18,0
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes  
Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.