



Hints and features:

- The Onyx NY-06 is a summer tyre for light trucks and transporters
- Its zigzag circumferential grooves with horizontal sipes guarantee very good grip on wet and dry roads
- The reinforced casing with 2 steel belts protects against damages and enables high loading capacities
- Its particularly wear-resistant rubber compound provides low heat generation and a long service life
- The variable pitch design guarantees ride comfort and low noise emission

REIFEN 225 / 65 R 16 C 8 PR, 112 / 110 T, TL, NY-06, M+S ONYX

Product-No.: 10165440

Technical Information:

Tyre size	225 / 65 R 16 C
TL / TT	TL
LI/SI	112 / 110 T
PR	8
Tread	NY-06
Manufacturer	Onyx
Specification	M+S
Recom. Rim	6.50J
Permissible rim	6J, 7J
Width [mm]	228
Outer diameter [mm]	698
Static radius [mm]	320
Rolling circumference [mm]	2115
Payload in kg at kph (1)	1120 / 190
Loadcapacity Twin Truck	1060 / 190
Inflation pressure [bar]	4,75
Weight [Kg]	13,77
Rolling resistance	D
Wet grip	С
Rolling Noise DB	72
Rolling Noise Level	В
Stud height [mm]	9,7
Zulassung	ECE 54, ECE 117
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.