Bohnenkamp Moving Professionals



Hints and features:

- The Sailun SAW1 is a truck winter tyre for steering axles but is also suitable for trailers
- The wide tread pattern and the tread pattern with 5 main grooves enable very good and safe handling on snow and ice
- Jagged sipes increase the contact area with the road and enhance the grip
- The sipe design and the shoulder grooves open on the sides reliably deflect water and snow
- The special rubber compound keeps its positive characteristics even at low temperatures

REIFEN 385 / 65 R 22.5 20 PR, 160 K (158 L), TL, SAW1, 3PMSF SAILUN (VA)

Product-No.: 11066388

Technical Information:

Tyre size	385 / 65 R 22.5
TL/TT	TL
LI / SI	160 K (158 L)
PR	20
Tread	SAW1
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	11.75
Permissible rim	12.25
Width [mm]	385
Outer diameter [mm]	1072
Static radius [mm]	495,96
Rolling circumference [mm]	3103
Payload in kg at kph (1)	4500 / 110
Payload in kg at kph (2)	4250 / 120
Inflation pressure [bar]	9,00
Weight [Kg]	75,93
Rolling resistance	E
Wet grip	С
Rolling Noise DB	74
Rolling Noise Level	В
Stud height [mm]	15,0
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.