



REIFEN 13 R 22.5
18 PR, 156 / 150 L, TL, S815, 3PMSF
SAILUN (VA / HA / TR)

Product-No.: 11066294

Technical Information:

Tyre size	13 R 22.5
TL / TT	TL
LI / SI	156 / 150 L
PR	18
Tread	S815
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	9.75
Permissible rim	9.00
Width [mm]	330
Outer diameter [mm]	1124
Static radius [mm]	520,56
Rolling circumference [mm]	3272
Payload in kg at kph (1)	4000 / 120
Loadcapacity Twin Truck	3350 / 120
Inflation pressure [bar]	8,75
Weight [Kg]	72,84
Rolling resistance	D
Wet grip	C
Rolling Noise DB	73
Rolling Noise Level	B
Stud height [mm]	17,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

Hints and features:

- The Sailun S815 is a truck tyre for all axles, mainly for use on building sites
- Zigzag-shaped circumferential grooves provide good traction and prevent stones from penetrating the tyre
- The deep shoulder groove reduces heat build-up and increases traction
- Sidewall guards protect the casing from damages
- The sturdy rubber compound and high tread pattern depth guarantee a long service life for the tyre