





## Hints and features:

- The Sailun SDO1 is a truck tyre for drive axles of vehicles used in construction and forestry work
- Its rough block tread pattern provides very good off-road traction
- The open tyre shoulder guarantees excellent stability and slow, even wear
- Due to its high tread pattern depth and the cut-resistant rubber compound, the tyre is very durable

REIFEN 13 R 22.5 18 PR, 156 / 150 G, TL, SDO1, 3PMSF SAILUN (HA), POR

Product-No.: 11066296

## **Technical Information:**

Tyre size	13 R 22.5
TL/TT	TL
LI/SI	156 / 150 G
PR	18
Tread	SDO1
Manufacturer	Sailun
Specification	3PMSF, POR
Recom. Rim	9.75
Permissible rim	9.00
Width [mm]	330
Outer diameter [mm]	1136
Static radius [mm]	520,56
Payload in kg at kph (1)	4000 / 90
Loadcapacity Twin Truck	3350 / 90
Inflation pressure [bar]	8,75
Weight [Kg]	77,42
Stud height [mm]	23,5
Zulassung	ECE 54
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.