



REIFEN 440 / 80 R 24
154 A8 / 149 D, TL, MULTIUSE 550, M+S
STEEL BELTED, BLOCK PROFIL (16.9R24),
ECE106

Product-No.: 15284072

Technical Information:

Tyre size	440 / 80 R 24
TL / TT	TL
LI / SI	154 A8 / 149 D
Tread	Multiuse 550
Manufacturer	Alliance
Specification	M+S, Steel Belted
Recom. Rim	DW14L
Width [mm]	441
Outer diameter [mm]	1319
Static radius [mm]	593
Rolling circumference [mm]	3913
Payload in kg at kph (1)	3750 / 40
Payload in kg at kph (2)	3250 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	100,4
Tyre content 75% [litre]	240,07
Stud height [mm]	26,6
Number of studs	14x2
Zulassung	ECE 106
M+S	M+S
Direction bound	Yes

Hints and features:

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres
- Steel belt reinforcement for high load capacity and protection against punctures
- With M+S identification