# Bohnenkamp Moving Professionals

## 



#### Hints and features:

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres
- Steel belt reinforcement for high load capacity and protection against punctures
- With M+S identification

## REIFEN 540 / 80 R 38 172 A8 / 167 D, TL, MULTIUSE 550, M+S STEEL BELTED, BLOCK PROFIL, (20.8R38), ECE106

### Product-No.: 15284162

#### **Technical Information:**

Tyre size	540 / 80 R 38
TL / TT	TL
LI / SI	172 A8 / 167 D
Tread	Multiuse 550
Manufacturer	Alliance
Specification	M+S, Steel Belted
Recom. Rim	DW18
Width [mm]	546
Outer diameter [mm]	1824
Static radius [mm]	835
Rolling circumference [mm]	5503
Payload in kg at kph (1)	6300 / 40
Payload in kg at kph (2)	5450 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	195
Tyre content 75% [litre]	541,05
Stud height [mm]	30,0
Number of studs	48x2
Zulassung	ECE 106
M+S	M+S
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.