

SEMPERIT 
Seit 1906.



Hints and features:

- The Semperit Worker D2 is a truck tyre for the drive axle for mixed on- and off-road use
- It is characterised by excellent traction due to the optimum tread pattern design
- The ideal tread pattern symmetry together with the abrasion-resistant rubber compound ensure even wear and a long service life

REIFEN 13 R 22.5
156 / 150 K, TL, WORKER D2, 3PMSF
SEMPERIT (HA)

Product-No.: 10966310

Technical Information:

Tyre size	13 R 22.5
TL / TT	TL
LI / SI	156 / 150 K
Tread	Worker D2
Manufacturer	Semperit
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width [mm]	330
Outer diameter [mm]	1146
Static radius [mm]	521
Rolling circumference [mm]	3428
Payload in kg at kph (1)	4000 / 110
Loadcapacity Twin Truck	3350 / 110
Inflation pressure [bar]	9,00
Weight [Kg]	74,29
Rolling resistance	D
Wet grip	B
Rolling Noise DB	75
Rolling Noise Level	B
Stud height [mm]	19,6
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.