





Hints and features:

- The BKT Agrimax Force is an IF tyre for high-performance tractors with more than 250 hp
- It carries 20% higher load capacity at the same inflation pressure or the same payload at 20% less inflation pressure compared with a standard tyre
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- The strong polyester casing ensures good traction and stability on all terrains and a long service life for the tyre
- The tyre guarantees ride comfort in the field and on the road without the need to adapt the inflation pressure

REIFEN IF 650 / 65 R 38 169 D, TL, AGRIMAX FORCE ECE106

Product-No.: 15727187

Technical Information:

Tyre size	IF 650 / 65 R 38
TL / TT	TL
LI/SI	169 D
Tread	Agrimax Force
Manufacturer	BKT
Recom. Rim	DW23B
Width [mm]	650
Outer diameter [mm]	1830
Static radius [mm]	830
Rolling circumference [mm]	5510
Payload in kg at kph (1)	5800 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	250,83
Stud height [mm]	58,0
Number of studs	20x2
Zulassung	ECE 106
Tyre technology	IF
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.