





REIFEN 710 / 70 R 38 178 A8 / 175 D, TL, AGRIMAX RT 765M ECE106

Product-No.: 15726959

## **Technical Information:**

Tyre size	710 / 70 R 38
TL / TT	TL
LI / SI	178 A8 / 175 D
Tread	Agrimax RT 765M
Manufacturer	BKT
Recom. Rim	DW23B
Permissible rim	DW25B
Width [mm]	716
Outer diameter [mm]	1959
Static radius [mm]	859
Rolling circumference [mm]	5751
Payload in kg at kph (1)	7500 / 40
Payload in kg at kph (1) Payload in kg at kph (2)	7500 / 40 6900 / 65
Payload in kg at kph (2)	6900 / 65
Payload in kg at kph (2) Inflation pressure [bar]	6900 / 65 3,20
Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg]	6900 / 65 3,20 304,75
Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre]	6900 / 65 3,20 304,75 862,5
Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre] Stud height [mm]	6900 / 65 3,20 304,75 862,5 58,5

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.