



Hints and features:

- The MRL MIM 374 is an agricultural tyre for tractors, which can also be used on backhoe loaders and agricultural trailers
- Its curved lugs with wide spaces provide good traction, ride comfort, self-cleaning and a long service life
- The especially wide lugs enable good ground contact for excellent traction on towing machines

REIFEN 7 - 16 4 PR, TT, MIM 374 ECE106

Product-No.: 19800287

## **Technical Information:**

Tyre size	7 - 16
TL/TT	TT
LI/SI	4 PR
PR	4
Tread	MIM 374
Manufacturer	MRL
Recom. Rim	6.00
Width [mm]	183
Outer diameter [mm]	742
Static radius [mm]	335
Rolling circumference [mm]	2190
Rolling circumference [mm] Payload in kg at kph (1)	2190 387 / 30
Payload in kg at kph (1)	387 / 30
Payload in kg at kph (1) Payload in kg at kph (2)	387 / 30 345 / 40
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar]	387 / 30 345 / 40 1,60
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg]	387 / 30 345 / 40 1,60 12
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre]	387 / 30 345 / 40 1,60 12 28
Payload in kg at kph (1) Payload in kg at kph (2) Inflation pressure [bar] Weight [Kg] Tyre content 75% [litre] Stud height [mm]	387 / 30 345 / 40 1,60 12 28 17,0

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.