



REIFEN 225 / 75 R 17.5
16 PR, 129 / 127 M, TL, SDR1, 3PMSF
SAILUN (HA)

Product-No.: 11066118

Technical Information:

| | |
|----------------------------|-----------------|
| Tyre size | 225 / 75 R 17.5 |
| TL / TT | TL |
| LI / SI | 129 / 127 M |
| PR | 16 |
| Tread | SDR1 |
| Manufacturer | Sailun |
| Specification | 3PMSF |
| Recom. Rim | 6.75 |
| Permissible rim | 7.5 |
| Width [mm] | 225 |
| Outer diameter [mm] | 783 |
| Static radius [mm] | 366,11 |
| Rolling circumference [mm] | 2388 |
| Payload in kg at kph (1) | 1850 / 130 |
| Loadcapacity Twin Truck | 1750 / 130 |
| Inflation pressure [bar] | 7,25 |
| Weight [Kg] | 28,75 |
| Rolling resistance | E |
| Wet grip | B |
| Rolling Noise DB | 73 |
| Rolling Noise Level | A |
| Stud height [mm] | 15,0 |
| Zulassung | ECE 54, ECE 117 |
| M+S | M+S |
| 3PMSF | 3PMSF |

Hints and features:

- The Sailun SDR1 is a truck tyre for drive axles for local and regional traffic
- The widened tread grooves provide good self-cleaning and good grip in all weather conditions
- A rib runs between the tread blocks for improved rigidity and resulting reduced wear
- Its wide contact area guarantees very good driving stability with optimum grip