Bohnenkamp Moving Professionals





Hints and features:

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications
- It is particularly suitable for state-of-theart contractors in winter operations
- The tyre offers excellent grip in the field on snow and ice, even without snow chains
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions
- The strong casing ensures durability and a long service life

REIFEN 600 / 65 R 28 165 A8 / 160 D, TL, RIDEMAX IT 697, M+S ECE106

Product-No.: 15775063

Technical Information:

Tyre size	600 / 65 R 28
TL/TT	TL
LI / SI	165 A8 / 160 D
Tread	Ridemax IT 697
Manufacturer	BKT
Specification	M+S
Recom. Rim	W18L
Permissible rim	DW20B
Width [mm]	591
Outer diameter [mm]	1491
Static radius [mm]	684
Rolling circumference [mm]	4509
Payload in kg at kph (1)	5150 / 40
Payload in kg at kph (2)	4500 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	162
Stud height [mm]	30,5
Number of studs	30x2
Zulassung	ECE 106
M+S	M+S
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.