



REIFEN 315 / 60 R 22.5
152 / 148 L, TL, HAKKA TRUCK DRIVE, 3PMSF
NOKIAN (HA)

Product-No.: 17466361

Technical Information:

Tyre size	315 / 60 R 22.5
TL / TT	TL
LI / SI	152 / 148 L
Tread	Hakka Truck Drive
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width [mm]	311
Outer diameter [mm]	963
Static radius [mm]	450
Rolling circumference [mm]	2927
Payload in kg at kph (1)	3550 / 120
Loadcapacity Twin Truck	3150 / 120
Inflation pressure [bar]	9,00
Weight [Kg]	58,7
Rolling resistance	C
Wet grip	C
Rolling Noise DB	76
Rolling Noise Level	B
Stud height [mm]	15,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
Direction bound	Yes

Hints and features:

- The Nokian Hakka Truck Drive is an all-season tyre for drive axles for regional and long-distance transport
- Its open V-shaped tread pattern with efficient sipes provides a secure grip in wintry conditions and good self-cleaning properties
- The tyre wears evenly and has a long service life
- It is equipped with DSI (Driving Safety Indication), which reliably indicates the remaining tread on the tyre

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.