



REIFEN 560 / 60 R 22.5
165 D / 162 E, TL, X POWER FLR 333
STEEL BELTED, ECE106

Product-No.: 19812585

Technical Information:

Tyre size	560 / 60 R 22.5
TL / TT	TL
LI / SI	165 D / 162 E
Tread	X POWER FLR 333
Manufacturer	MRL
Specification	Steel Belted
Recom. Rim	AG16
Width [mm]	543
Outer diameter [mm]	1244
Static radius [mm]	549
Rolling circumference [mm]	3767
Payload in kg at kph (1)	5150 / 65
Payload in kg at kph (2)	4750 / 70
Inflation pressure [bar]	5,00
Weight [Kg]	124
Stud height [mm]	19,2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- The MRL X POWER FLR 333 was developed for agricultural trailers, tankers and spreaders
- The tyre offers very high load capacities with low soil compaction at the same time
- Its block tread pattern provides good rolling characteristics for low fuel consumption, good self-cleaning and ride comfort

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.