





Hints and features:

- The Nokian E-Truck Drive is an allseason tyre for truck drive axles used in regional and long-distance transport
- Its tread pattern provides good grip, even in different road and weather conditions
- Its block pattern guarantees good traction
- The tread pattern wears evenly and ensures a long service life for the tyre
- Due to the low rolling resistance, the tyre provides low fuel consumption and good ride comfort

REIFEN 315 / 70 R 22.5 154 / 150 L (152/148 M), TL, E-TRUCK DRIVE, 3PMSF NOKIAN (HA)

Product-No.: 17466516

Technical Information:

Tyre size	315 / 70 R 22.5
TL/TT	TL
LI/SI	154 / 150 L (152 / 148 M)
Tread	E-Truck Drive
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width [mm]	314
Outer diameter [mm]	1027
Static radius [mm]	474
Rolling circumference [mm]	3122
Payload in kg at kph (1)	3750 / 120
Payload in kg at kph (2)	3550 / 130
Loadcapacity Twin Truck	3350 / 120 (3150 / 130)
Inflation pressure [bar]	9,00
Weight [Kg]	67
Rolling resistance	С
Wet grip	С
Rolling Noise DB	73
Rolling Noise Level	A
Stud height [mm]	17,5
M+S	M+S
3PMSF	3PMSF
LI 4	148

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.