



REIFEN 405 / 70 R 20
155 A2 / 143 B, TL, SP-T9, M+S
L2 / E2, ECE106

Product-No.: 11285090

Technical Information:

Tyre size	405 / 70 R 20
TL / TT	TL
LI / SI	155 A2 / 143 B
Tread	SP-T9
Manufacturer	Dunlop
Specification	M+S, L2/E2
Width [mm]	403
Outer diameter [mm]	1093
Static radius [mm]	487
Rolling circumference [mm]	3240
Payload in kg at kph (1)	3875 / 10
Payload in kg at kph (2)	2725 / 50
Inflation pressure [bar]	3,75
Weight [Kg]	70
Tyre content 75% [litre]	160
Stud height [mm]	19,0
M+S	M+S
TRA Code	L2, E2

Hints and features:

- The Dunlop SP-T9 is a radial MPT tyre for loaders, graders and other vehicles
- It is excellently suited to the mixed application on and off the road
- Tread center blocks provide smooth riding on the road, lugs on the outside of the tread grant excellent traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.