



Hints and features:

- The Maxam MS503 is a radial EM tyre for wheel loaders, graders and similar vehicles for various applications
- Its open deep tread pattern (L5) provides outstanding traction and high wear resistance on all surfaces
- The reinforced bead, tyre shoulder and sidewall as well as the thick undertread protect the tyre against cuts, punctures and other damages
- The wide and flat footprint offers stability and low and even wear
- Special stone- and mud ejectors between the tread lugs enable very good self-cleaning

REIFEN 17.5 R 25 182 A2, TL, MS503 L5T**, CUT RESISTANT

Product-No.: 11085112

Technical Information:

Tyre size	17.5 R 25
TL / TT	TL
LI / SI	182 A2
Tread	MS503
Manufacturer	Maxam
Specification	L5T, **, C.R.
Recom. Rim	14.00/1.5
Width [mm]	433
Outer diameter [mm]	1.408
Static radius [mm]	647
Rolling circumference [mm]	4242
Payload in kg at kph (1)	8500 / 10
Inflation pressure [bar]	6,50
Weight [Kg]	241
Stud height [mm]	64,0
Star Rating	**
TRA Code	L5T

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.