

WINDPOWER
Get Your Job Done



Hints and features:

- High traction tread pattern with extra wide contact area
- The combination of transversal and longitudinal grooves offers excellent grip, high ride comfort and self-cleaning
- Optimised tread pattern compound
- Extra-sturdy and durable rubber compound
- Suitable for wheel loaders, dumpers & graders
- Only approved for mounting on multi-part rim

REIFEN 750 / 65 R 25
202 A2 / 190 B, TL, W 733
E3**, HEAT RESISTANT

Product-No.: 10485145

Technical Information:

Tyre size	750 / 65 R 25
TL / TT	TL
LI / SI	202 A2 / 190 B
Tread	W 733
Manufacturer	Windpower
Specification	E3, **, H.R.
Recom. Rim	24.00/3.0
Width [mm]	750
Outer diameter [mm]	1610
Static radius [mm]	708
Payload in kg at kph (1)	15000 / 10
Payload in kg at kph (2)	10600 / 50
Inflation pressure [bar]	4,75
Weight [Kg]	456,1
Stud height [mm]	44,0
Zulassung	nicht notwendig
Star Rating	**
TRA Code	E3

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.