





## Hints and features:

- The Nokian Hakka Truck Trailer is a truck trailer tyre for regional and long haul
- The sturdy tread pattern with 4 open grooves provides good grip and self cleaning
- Stone ejectors prevent the penetration of small stones and protect the tread from damages
- The wide tyre shoulder grants stability, lateral hold and minimizes damages caused by chafing
- Tight and deep composite sipes on the tread ribs provide excellent grip and stability even in the first stages of wear

REIFEN 275 / 70 R 22.5 148 / 145 L, TL, HAKKA TRUCK TRAILER, 3PMSF NOKIAN (TR)

Product-No.: 17466318

## **Technical Information:**

Tyre size	275 / 70 R 22.5
TL / TT	TL
LI/SI	148 / 145 L
Tread	Hakka Truck Trailer
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	8.25
Permissible rim	7.50
Width [mm]	273
Outer diameter [mm]	969
Static radius [mm]	450
Rolling circumference [mm]	2945
Payload in kg at kph (1)	3150 / 120
Loadcapacity Twin Truck	2900 / 120
Inflation pressure [bar]	9,00
Weight [Kg]	54,5
Rolling resistance	D
Wet grip	С
Rolling Noise DB	68
Rolling Noise Level	A
Stud height [mm]	14,5
Zulassung	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.