



#### Hints and features:

- The Nokian Hakka Truck Trailer is a truck trailer tyre for regional and long haul
- The sturdy tread pattern with 4 open grooves provides good grip and self cleaning
- Stone ejectors prevent the penetration of small stones and protect the tread from damages
- The wide tyre shoulder grants stability, lateral hold and minimizes damages caused by chafing
- Tight and deep composite sipes on the tread ribs provide excellent grip and stability even in the first stages of wear

REIFEN 385 / 65 R 22.5  
160 K (158 L), TL, HAKKA TRUCK TRAILER,  
3PMSF  
NOKIAN (TR)

**Product-No.: 17466449**

#### Technical Information:

Tyre size	385 / 65 R 22.5
TL / TT	TL
LI / SI	160 K (158 L)
Tread	Hakka Truck Trailer
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	11.75
Permissible rim	12.25
Width [mm]	380
Outer diameter [mm]	1084
Static radius [mm]	501
Rolling circumference [mm]	3295
Payload in kg at kph (1)	4500 / 110
Payload in kg at kph (2)	4250 / 120
Inflation pressure [bar]	9,00
Weight [Kg]	74
Rolling resistance	B
Wet grip	C
Rolling Noise DB	67
Rolling Noise Level	A
Stud height [mm]	15,5
Zulassung	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF