# Bohnenkamp Moving Professionals



#### Hints and features:

- The Galaxy Rock Mine Lug is a bias tyre for EM applications, designed for underground mining operations
- It is excellently suited tippers and medium-sized forklifts working on the most difficult soil conditions
- The tyre is characterised by very high resistance against tread wear and optimally protected against sidewall damages

## REIFEN 9.00 - 20 14 PR, TT, ROCK MINE LUG E3/L3

## Product-No.: 12085010

### **Technical Information:**

Tyre size	9.00 - 20
TL / TT	ТТ
LI / SI	14 PR
PR	14
Tread	Rock Mine Lug
Manufacturer	Galaxy
Specification	E3/L3
Recom. Rim	7.0
Width [mm]	276
Outer diameter [mm]	1050
Static radius [mm]	436
Rolling circumference [mm]	3029
Payload in kg at kph (1)	6268 / 25
Inflation pressure [bar]	7,00
Weight [Kg]	46,2
Stud height [mm]	20,6
Zulassung	nicht notwendig
TRA Code	E3, L3

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.