



REIFEN 260 / 55 - 12
14 PR, 110 A8 / 122 A8, TL, LG 306,
RASENPROFIL
(23x10.50-12), ECE106

Product-No.: 10000096

Technical Information:

Tyre size	260 / 55 - 12
TL / TT	TL
LI / SI	110 A8 / 122 A8
PR	14
Tread	LG 306
Manufacturer	BKT
Recom. Rim	8.5
Permissible rim	7.00
Width [mm]	260
Outer diameter [mm]	585
Static radius [mm]	262
Rolling circumference [mm]	1697
Payload in kg at kph (1)	1060 / 40
Payload in kg at kph (2)	1500 / 40
Inflation pressure [bar]	6,00
Weight [Kg]	11,86
Stud height [mm]	10,0
Zulassung	ECE 106

Hints and features:

- Grass tyre with excellent contact area for low soil compaction
- Rounded tyre shoulder for optimal turf protection
- High tread pattern depth in conjunction with a rugged casing for high mileage and protection against damage (punctures)

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.