



REIFEN 225 / 70 R 15 C  
8 PR, 112 / 110 R, TL, MR200, M+S  
MIRAGE

**Product-No.: 10165900**

**Technical Information:**

Tyre size	225 / 70 R 15 C
TL / TT	TL
LI / SI	112 / 110 R
PR	8
Tread	MR200
Manufacturer	Mirage
Specification	M+S
Recom. Rim	6.50
Permissible rim	6J, 7J
Width [mm]	228
Outer diameter [mm]	697
Static radius [mm]	317
Rolling circumference [mm]	2112
Payload in kg at kph (1)	1120 / 170
Loadcapacity Twin Truck	1060 / 170
Inflation pressure [bar]	4,50
Weight [Kg]	13,8
Rolling resistance	D
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Stud height [mm]	10,2
Zulassung	ECE 54, ECE 117
M+S	M+S

**Hints and features:**

- The Mirage MR200 is a summer tyre for light trucks and transporters
- Its zigzag vertical grooves with horizontal sipes grant excellent grip on wet and dry road
- The reinforced casing with 2 steel belts protect the tyres from damages and enables high loading capacities
- Its abrasion-resistant tread compound provides low heat generation and long service life of the tyre
- The variable pitch pattern grants riding comfort and low noise emission