# Bohnenkamp Moving Professionals



### Hints and features:

- The Mirage MR200 is a summer tyre for light trucks and transporters
- Its zigzag vertical grooves with horizontal sipes grant excellent grip on wet and dry road
- The reinforced casing with 2 steel belts protect the tyres from damages and enables high loading capacities
- Its abrasion-resistant tread compound provides low heat generation and long service life of the tyre
- The variable pitch pattern grants riding comfort and low noise emission

## REIFEN 175 R 14 C 8 PR, 99 / 98 R, TL, MR200, M+S MIRAGE

## Product-No.: 10165910

### **Technical Information:**

Tyre size	175 R 14 C
TL / TT	TL
LI / SI	99 / 98 R
PR	8
Tread	MR200
Manufacturer	Mirage
Specification	M+S
Recom. Rim	5J
Permissible rim	4.50J, 5.50J
Width [mm]	178
Outer diameter [mm]	634
Static radius [mm]	289
Rolling circumference [mm]	1921
Payload in kg at kph (1)	775 / 170
Loadcapacity Twin Truck	750 / 170
Inflation pressure [bar]	4,50
Weight [Kg]	8,9
Rolling resistance	D
Wet grip	С
Rolling Noise DB	72
Rolling Noise Level	В
Stud height [mm]	7,3
Zulassung	ECE 117, ECE 54
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.