



REIFEN 175 / 65 R 14 C
6 PR, 90 / 88 T, TL, MR200, M+S
MIRAGE

Product-No.: 10165912

Technical Information:

Tyre size	175 / 65 R 14 C
TL / TT	TL
LI / SI	90 / 88 T
PR	6
Tread	MR200
Manufacturer	Mirage
Specification	M+S
Recom. Rim	5J
Permissible rim	5.50J
Width [mm]	177
Outer diameter [mm]	584
Static radius [mm]	269
Rolling circumference [mm]	1770
Payload in kg at kph (1)	600 / 190
Loadcapacity Twin Truck	560 / 190
Inflation pressure [bar]	3,75
Weight [Kg]	7,1
Rolling resistance	D
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Stud height [mm]	8,1
Zulassung	ECE 117, ECE 54
M+S	M+S

Hints and features:

- The Mirage MR200 is a summer tyre for light trucks and transporters
- Its zigzag vertical grooves with horizontal sipes grant excellent grip on wet and dry road
- The reinforced casing with 2 steel belts protect the tyres from damages and enables high loading capacities
- Its abrasion-resistant tread compound provides low heat generation and long service life of the tyre
- The variable pitch pattern grants riding comfort and low noise emission