



REIFEN 195 / 65 R 16 C  
8 PR, 104 / 102 T, TL, MR200, M+S  
MIRAGE

**Product-No.: 10165916**

**Technical Information:**

Tyre size	195 / 65 R 16 C
TL / TT	TL
LI / SI	104 / 102 T
PR	8
Tread	MR200
Manufacturer	Mirage
Specification	M+S
Recom. Rim	6J
Permissible rim	5.5J
Width [mm]	201
Outer diameter [mm]	650
Static radius [mm]	305
Rolling circumference [mm]	2000
Payload in kg at kph (1)	900 / 190
Loadcapacity Twin Truck	850 / 190
Inflation pressure [bar]	4,75
Weight [Kg]	11,3
Rolling resistance	D
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Stud height [mm]	9,7
Zulassung	ECE 117, ECE 54
M+S	M+S

**Hints and features:**

- The Mirage MR200 is a summer tyre for light trucks and transporters
- Its zigzag vertical grooves with horizontal sipes grant excellent grip on wet and dry road
- The reinforced casing with 2 steel belts protect the tyres from damages and enables high loading capacities
- Its abrasion-resistant tread compound provides low heat generation and long service life of the tyre
- The variable pitch pattern grants riding comfort and low noise emission