



REIFEN 205 / 65 R 16 C 8 PR, 107 / 105 T, TL, MR200, M+S MIRAGE

Product-No.: 10165918

Technical Information:

Tyre size	205 / 65 R 16 C
TL / TT	TL
LI / SI	107 / 105 T
PR	8
Tread	MR200
Manufacturer	Mirage
Specification	M+S
Recom. Rim	6J
Permissible rim	5.50J, 6.50J
Width [mm]	209
Outer diameter [mm]	672
Static radius [mm]	309
Rolling circumference [mm]	2036
Payload in kg at kph (1)	975 / 190
Loadcapacity Twin Truck	925 / 190
Inflation pressure [bar]	4,75
Weight [Kg]	12,5
Rolling resistance	D
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Stud height [mm]	9,7
Zulassung	ECE 117, ECE 54
M+S	M+S

Hints and features:

- The Mirage MR200 is a summer tyre for light trucks and transporters
- Its zigzag vertical grooves with horizontal sipes grant excellent grip on wet and dry road
- The reinforced casing with 2 steel belts protect the tyres from damages and enables high loading capacities
- Its abrasion-resistant tread compound provides low heat generation and long service life of the tyre
- The variable pitch pattern grants riding comfort and low noise emission