



REIFEN 215 / 65 R 16 C
8 PR, 109 / 107 T, TL, MR200, M+S
MIRAGE

Product-No.: 10165920

Technical Information:

Tyre size	215 / 65 R 16 C
TL / TT	TL
LI / SI	109 / 107 T
PR	8
Tread	MR200
Manufacturer	Mirage
Specification	M+S
Recom. Rim	6.50J
Permissible rim	6J, 7J
Width [mm]	221
Outer diameter [mm]	686
Static radius [mm]	315
Rolling circumference [mm]	2079
Payload in kg at kph (1)	1030 / 190
Loadcapacity Twin Truck	975 / 190
Inflation pressure [bar]	4,75
Weight [Kg]	13,2
Rolling resistance	D
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Stud height [mm]	9,7
Zulassung	ECE 117, ECE 54
M+S	M+S

Hints and features:

- The Mirage MR200 is a summer tyre for light trucks and transporters
- Its zigzag vertical grooves with horizontal sipes grant excellent grip on wet and dry road
- The reinforced casing with 2 steel belts protect the tyres from damages and enables high loading capacities
- Its abrasion-resistant tread compound provides low heat generation and long service life of the tyre
- The variable pitch pattern grants riding comfort and low noise emission