



REIFEN 215 / 65 R 15 C 6 PR, 104 / 102 T, TL, MR-700 AS, 3PMSF MIRAGE

Product-No.: 10165864

Technical Information:

Tyre size	215 / 65 R 15 C
TL / TT	TL
LI / SI	104 / 102 T
PR	6
Tread	MR-700 AS
Manufacturer	Mirage
Specification	3PMSF
Recom. Rim	6.50J
Permissible rim	6J, 7J
Width [mm]	221
Outer diameter [mm]	661
Static radius [mm]	302
Rolling circumference [mm]	2003
Payload in kg at kph (1)	900 / 190
Loadcapacity Twin Truck	850 / 190
Inflation pressure [bar]	3,75
Weight [Kg]	11,6
Rolling resistance	D
Wet grip	D
Rolling Noise DB	73
Rolling Noise Level	B
Stud height [mm]	9,7
Zulassung	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF

Hints and features:

- The Mirage MR-700 AS is an all season tyre for commercial vans
- The pattern is providing a very good performance on dry, wet and snowy roads
- Thre digzag grooves protect from aquaplaning and grant driving safety on difficult weather conditions
- Small sipes on the ribs improve the grip at rain and snow
- The high-grip silica compound grant good driving performance and low rolling resistance