



Hints and features:

- The Mirage MR-700 AS is an all season tyre for commercial vans
- The pattern is providing a very good performance on dry, wet and snowy roads
- Thre digzag grooves protect from aquaplaning and grant driving safety on difficult weather conditions
- Small sipes on the ribs improve the grip at rain and snow
- The high-grip silica compound grant good driving performance and low rolling resistance

REIFEN 215 / 75 R 16 C 10 PR, 116 / 114 R, TL, MR-700 AS, 3PMSF MIRAGE

Product-No.: 10165884

Technical Information:

| Tyre size | 215 / 75 R 16 C |
|----------------------------|------------------|
| TL/TT | TL |
| LI / SI | 116 / 114 R |
| PR | 10 |
| Tread | MR-700 AS |
| Manufacturer | Mirage |
| Specification | 3PMSF |
| Recom. Rim | 6J |
| Permissible rim | 5.50J, 6.50J, 7J |
| Width [mm] | 216 |
| Outer diameter [mm] | 728 |
| Static radius [mm] | 332 |
| Rolling circumference [mm] | 2206 |
| Payload in kg at kph (1) | 1250 / 170 |
| Loadcapacity Twin Truck | 1180 / 170 |
| Inflation pressure [bar] | 5,25 |
| Weight [Kg] | 14,7 |
| Rolling resistance | D |
| Wet grip | D |
| Rolling Noise DB | 73 |
| Rolling Noise Level | В |
| Stud height [mm] | 9,7 |
| Zulassung | ECE 117, ECE 54 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| | |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.