



REIFEN 205 / 65 R 16 C  
8 PR, 107 / 105 T, TL, MR-W600, 3PMSF  
MIRAGE

**Product-No.: 10165810**

**Technical Information:**

|                            |                 |
|----------------------------|-----------------|
| Tyre size                  | 205 / 65 R 16 C |
| TL / TT                    | TL              |
| LI / SI                    | 107 / 105 T     |
| PR                         | 8               |
| Tread                      | MR-W600         |
| Manufacturer               | Mirage          |
| Specification              | 3PMSF           |
| Recom. Rim                 | 6J              |
| Permissible rim            | 5.50J, 6.50J    |
| Width [mm]                 | 209             |
| Outer diameter [mm]        | 672             |
| Static radius [mm]         | 309             |
| Rolling circumference [mm] | 2036            |
| Payload in kg at kph (1)   | 975 / 190       |
| Loadcapacity Twin Truck    | 925 / 190       |
| Inflation pressure [bar]   | 4,75            |
| Weight [Kg]                | 12,3            |
| Rolling resistance         | D               |
| Wet grip                   | D               |
| Rolling Noise DB           | 73              |
| Rolling Noise Level        | B               |
| Stud height [mm]           | 9,7             |
| Zulassung                  | ECE 117, ECE 54 |
| M+S                        | M+S             |
| 3PMSF                      | 3PMSF           |
| Direction bound            | Yes             |

**Hints and features:**

- The Mirage MR-W600 is a studdable winter tyre for commercial vans
- The high void directional tread pattern provides good ground contact and safe driving under winter conditions
- The construction of sipes and sawtooth shaped main grooves increases grip and steering control on snowy and icy roads
- The special winter compound enables great grip on snowy, icy and wet roads and an excellent performance at low temperatures