



Hints and features:

- BKT's Skid Power SK tyre is a newlydeveloped wide-wall skid steer loader tyre
- With sidewall and rim guard protectors, the Skid Power SK is ideal for performance-oriented and priceconscious use on skid steer loaders like the Bobcat and other similar vehicles

RAD 10 - 16.5 BKT SKID POWER SK 10 PR, 1400 KG - 10 KM/H, TL, 6/161/205, ET +50 8.25 X 16.5, RAL9006 SILBER, VS H, LINKS

Product-No.: 10000111

Technical Information:

Wheel size	10 - 16.5
LI / PR	120 A8, 10 PR
Tread	Skid Power SK
Manufacturer	BKT
Rim	8.25 x 16.5
Connection	6/161/205
Bolt hole execution	A2
Rim centering	BZ
ET	50
Width [mm]	270
Outer diameter [mm]	775
Static radius [mm]	355
Rolling circumference [mm]	2286
Direction	Links
Inflation pressure [bar]	5,20
Loadcapacity Tyre	1400 / 40
Loadcapacity Rim	2000 / 10
Loadcapacity compl. Wheel	1.400
Tread depth [mm]	15,0
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	40,28

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.