



## Hints and features:

- The Security TR 603 is a professional tyre for use on car trailers
- The tyre is reinforced by additional casing plies and offers very good stability

REIFEN 165 R 13 C 96 N (94 / 92 R), TL, TR603, M+S SECURITY

Product-No.: 18366151

## **Technical Information:**

Tyre size	165 R 13 C
TL/TT	TL
LI/SI	96 N (94 / 92 R)
Tread	TR603
Manufacturer	Security
Specification	M+S
Recom. Rim	4.50
Width [mm]	165
Outer diameter [mm]	594
Static radius [mm]	278
Rolling circumference [mm]	1806
Payload in kg at kph (1)	710 / 140
Payload in kg at kph (2)	670 / 170
Loadcapacity Twin Truck	(630 / 170)
Inflation pressure [bar]	4,50
Weight [Kg]	9
Rolling resistance	D
Wet grip	С
Rolling Noise DB	72
Rolling Noise Level	В
Zulassung	ECE 54, ECE 117
M+S	M+S
LI 4	92

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.