



REIFEN 215 / 60 R 16 C  
8 PR, 108 / 106 R, TL, MR-W300, 3PMSF  
MIRAGE

Product-No.: 10165826

Technical Information:

Tyre size	215 / 60 R 16 C
TL / TT	TL
LI / SI	108 / 106 R
PR	8
Tread	MR-W300
Manufacturer	Mirage
Specification	3PMSF
Recom. Rim	6.50J
Permissible rim	6J, 7J
Width [mm]	221
Outer diameter [mm]	664
Static radius [mm]	306
Rolling circumference [mm]	2012
Payload in kg at kph (1)	1000 / 170
Loadcapacity Twin Truck	950 / 170
Inflation pressure [bar]	4,75
Weight [Kg]	12,7
Rolling resistance	D
Wet grip	D
Rolling Noise DB	73
Rolling Noise Level	B
Stud height [mm]	9,7
Zulassung	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF

Hints and features:

- The Mirage MR-W300 is a winter tyre for commercial vans
- Its block pattern with 3 zigzag grooves plus high-density sipes provide good grip on wet and cold road and under snow and ice conditions
- The special tread compound grants a low rolling resistance
- Its reinforced casing enables high loading capacities and a long service life

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes  
Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.