Bohnenkamp

📕 🛑 Moving Professionals

BKT



RAD 800 / 65 R 32 BKT RIDEMAX FL 615 185 D, TL, 10/281/335, B3, ET +30 27 X 32, RAL9006 SILBER

Product-No.: 10000420

Technical Information:

Wheel size	800 / 65 R 32
LI / PR	185 D
Tread	Ridemax FL 615
Manufacturer	BKT
Rim	TW 27 B x 32
Connection	10/281/335
Bolt hole execution	B3
Rim centering	BZ
ET	+30
Width [mm]	830
Outer diameter [mm]	1.853
Static radius [mm]	834
Rolling circumference [mm]	5624
Inflation pressure [bar]	3,60
Loadcapacity Tyre	9250 / 65
Loadcapacity Rim	13300 / 40
Loadcapacity compl. Wheel	9000 / 40
Tread depth [mm]	31,0
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	470,89

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.