

TRELLEBORG



REIFEN 520 / 85 R 38
155 A8 / 152 B, TL, TM 600
(20.8 R 38), DEMO, RISS IN DER
REIFENSCHULTER

Product-No.: 10000669

Technical Information:

Tyre size	520 / 85 R 38
TL / TT	TL
LI / SI	155 A8 / 152 B
Tread	TM600
Manufacturer	Trelleborg
Recom. Rim	18
Permissible rim	16
Width [mm]	536
Outer diameter [mm]	1.849
Static radius [mm]	825
Rolling circumference [mm]	5.510
Payload in kg at kph (1)	3875 / 40
Payload in kg at kph (2)	3550 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	184,36
Tyre content 75% [litre]	648
Stud width [mm]	51
Stud height [mm]	53,0
Direction bound	Yes

Hints and features:

- Protects turf and crops due to innovative tread pattern
- High load capacity
- Low soil compaction
- Optimal traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.