



REIFEN 400 / 70 R 20  
149 A8 / 149 B, TL, TH 400  
(16.0/70R20)

**Product-No.: 10001021**

#### Technical Information:

Tyre size	400 / 70 R 20
TL / TT	TL
LI / SI	149 A8 / 149 B
Tread	TH400
Manufacturer	Trelleborg
Recom. Rim	13
Permissible rim	12, 14
Width [mm]	395
Outer diameter [mm]	1.065
Static radius [mm]	475
Rolling circumference [mm]	3200
Payload in kg at kph (1)	3250 / 40
Payload in kg at kph (2)	3250 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	71,46
Zulassung	nicht notwendig
Direction bound	Yes

#### Hints and features:

- Agro-industrial tyre for telescopic handlers, excavators and skid steer loaders
- Ideal for use on hard ground and in biogas plants
- Allows high machine stability, even when boom is fully extended
- Maximum resistance to punctures and cuts

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.