## Bohnenkamp Moving Professionals

TRELLEBORG



## Hints and features:

- Protects turf and crops due to innovative tread pattern
- High load capacity
- Low soil compaction
- Optimal traction

REIFEN 280 / 85 R 28 118 A8 / 115 B, TL, TM 600 (11.2 R 28)

## Product-No.: 10001032

## **Technical Information:**

Tyre size	280 / 85 R 28
TL/TT	TL
LI / SI	118 A8 / 115 B
Tread	TM600
Manufacturer	Trelleborg
Recom. Rim	10
Permissible rim	9
Width [mm]	292
Outer diameter [mm]	1.187
Static radius [mm]	542
Rolling circumference [mm]	3580
Payload in kg at kph (1)	1320 / 40
Payload in kg at kph (2)	1215 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	48,81
Stud width [mm]	24
Stud height [mm]	39,0
Number of studs	22x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential

damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.