Bohnenkamp Moving Professionals

TRELLEBORG



Hints and features:

- Excellent soil protection thanks to its large contact area and rounded shoulders
- The structure of the lugs and the block tread pattern provide good traction as well as fast and effective self-cleaning
- High performance in the field and on the road
- Great ride comfort with low noise generation

REIFEN 600 / 55 R 26.5 165 D, TL, TWIN RADIAL

Product-No.: 10001037

Technical Information:

Tyre size	600 / 55 R 26.5
TL / TT	TL
LI / SI	165 D
Tread	Twin Radial
Manufacturer	Trelleborg
Recom. Rim	20.00
Width [mm]	636
Outer diameter [mm]	1.341
Static radius [mm]	605
Rolling circumference [mm]	4110
Payload in kg at kph (1)	5150 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	147,07
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.