



REIFEN 340 / 85 R 28  
127 A8 / 124 B, TL, TM 600  
(13.6 R 28)

**Product-No.: 10001051**

## Technical Information:

Tyre size	340 / 85 R 28
TL / TT	TL
LI / SI	127 A8 / 124 B
Tread	TM600
Manufacturer	Trelleborg
Recom. Rim	12
Permissible rim	11
Width [mm]	353
Outer diameter [mm]	1.289
Static radius [mm]	595
Rolling circumference [mm]	3885
Payload in kg at kph (1)	1750 / 40
Payload in kg at kph (2)	1600 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	67,4
Tyre content 75% [litre]	182
Stud width [mm]	36
Stud height [mm]	44,0
Number of studs	20x2
Zulassung	nicht notwendig
Direction bound	Yes

## Hints and features:

- Protects turf and crops due to innovative tread pattern
- High load capacity
- Low soil compaction
- Optimal traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.