



Hints and features:

- The TM 700 is an agricultural radial tyre
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance

REIFEN 280 / 70 R 16
112 A8 / 112 B, TL, TM 700

Product-No.: 10001066

Technical Information:

Tyre size	280 / 70 R 16
TL / TT	TL
LI / SI	112 A8 / 112 B
Tread	TM700
Manufacturer	Trelleborg
Recom. Rim	9
Permissible rim	8, 10
Width [mm]	282
Outer diameter [mm]	798
Static radius [mm]	355
Rolling circumference [mm]	2385
Payload in kg at kph (1)	1120 / 40
Payload in kg at kph (2)	1120 / 50
Inflation pressure [bar]	2,40
Weight [Kg]	24,30
Tyre content 75% [litre]	54,3
Stud width [mm]	34
Stud height [mm]	35,0
Number of studs	34x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.