





Hints and features:

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.
- The tyre is marked with the logo ""E-Ready"" on the sidewall."

REIFEN 480 / 70 R 28 143 A8 / 140 D, TL, AGRIMAX FACTOR ECE106

Product-No.: 10000973

Technical Information:

Tyre size	480 / 70 R 28
TL/TT	TL
LI/SI	143 A8 / 140 D
Tread	Agrimax Factor
Manufacturer	BKT
Recom. Rim	W15L
Permissible rim	W14L, W16L
Width [mm]	479
Outer diameter [mm]	1.421
Static radius [mm]	639
Rolling circumference [mm]	4239
Payload in kg at kph (1)	2725 / 40
Payload in kg at kph (2)	2500 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	113,05
Stud height [mm]	48,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.