



REIFEN 275 / 80 R 20  
134 K, TL, MULTIMAX MP 540, M+S  
(10.5R20), POR, ECE54

**Product-No.: 10001162**

#### Technical Information:

Tyre size	275 / 80 R 20
TL / TT	TL
LI / SI	134 K
Tread	Multimax MP 540
Manufacturer	BKT
Specification	M+S, POR
Recom. Rim	W9
Permissible rim	9
Width [mm]	270
Outer diameter [mm]	955
Static radius [mm]	443
Rolling circumference [mm]	2913
Payload in kg at kph (1)	2120 / 110
Inflation pressure [bar]	5,20
Weight [Kg]	41,60
Stud height [mm]	14,5
Zulassung	ECE 54
M+S	M+S

#### Hints and features:

- The BKT Multimax MP 540 was developed for multipurpose vehicles in municipality/maintenance applications
- Thanks to its reinforced, steel belted nylon casing, the tyre provides provides high load capacity at high speeds

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.