## Bohnenkamp Moving Professionals



Hints and features:

## REIFEN 420 / 80 R 46 170 A2 / 159 D , TL, AGRIMAX RT 855 (16.9 R 46), ECE106, DEMO 90%

## Product-No.: 72300158

## **Technical Information:**

| Tyre size                  | 420 / 80 R 46  |
|----------------------------|----------------|
| TL/TT                      | TL             |
| LI / SI                    | 170 A2 / 159 D |
| Tread                      | Agrimax RT 855 |
| Manufacturer               | ВКТ            |
| Recom. Rim                 | W13            |
| Permissible rim            | W12            |
| Width [mm]                 | 418            |
| Outer diameter [mm]        | 1840           |
| Static radius [mm]         | 863            |
| Rolling circumference [mm] | 5.641          |
| Payload in kg at kph (1)   | 6000 / 10      |
| Payload in kg at kph (2)   | 4375 / 65      |
| Inflation pressure [bar]   | 3,20           |
| Weight [Kg]                | 159,93         |
| Tyre content 75% [litre]   | 371,75         |
| Stud height [mm]           | 51,0           |
| Number of studs            | 26x2           |
| Zulassung                  | ECE 106        |
| Direction bound            | Yes            |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.